

**Amendments to the Claims:**

This listing of claims will replace all prior versions and listings of claims in the application:

**Listing of the Claims:**

1. (Currently Amended) A method comprising:
  - identifying a plurality of fork subgraph structures within a graph structure constructed for a plurality of executable instructions;
  - identifying a plurality of unifiable variables within each fork subgraph structure of said plurality of fork subgraph structures, which are not simultaneously used in said plurality of executable instructions;
  - constructing a dependence graph of said plurality of executable instructions;
  - using said dependence graph to identify at least one unifiable instruction of said plurality of executable instructions, within said plurality of fork subgraph structures; and
  - transferring said at least one unifiable instruction of said plurality of executable instructions from a tine of a corresponding fork subgraph structure of said plurality of fork subgraph structures to a handle of said

corresponding fork subgraph structure, said at least one unifiable instruction containing at least one unifiable variable of said plurality of unifiable variables.

2. (Currently Amended) The method according to claim 1, wherein identifying said plurality of unifiable variables further comprises:

constructing an interference graph structure for a plurality of local variables within said each fork subgraph structure, said plurality of local variables including said plurality of unifiable variables; and

identifying said plurality of unifiable variables as variables having non-overlapping live ranges within said interference graph structure.

3. (Original) The method according to claim 2, wherein said interference graph structure indicates which variables of said plurality of local variables are simultaneously used in said plurality of executable instructions and cannot be unified.

4. (Original) The method according to claim 1, wherein identifying said plurality of unifiable variables further comprises:

constructing a data dependence graph structure for said plurality of executable instructions; and

identifying said plurality of unifiable variables using said data dependence graph structure.

5. (Original) The method according to claim 1, wherein said transferring further comprises:

initializing a flag for said at least one unifiable instruction; and  
unifying each unifiable variable within said at least one unifiable instruction.

6. (Previously Presented) The method according to claim 5, wherein said transferring further comprises:

removing said at least one unifiable instruction from subsequent tines of said corresponding fork subgraph structure.

7. (Previously Presented) The method according to claim 4, wherein said data dependence graph structure contains a plurality of dependence arcs, each dependence arc connecting two instructions of said plurality of executable

instructions contained within said tine of said corresponding fork subgraph structure.

8. (Currently Amended) A system comprising:

means for identifying a plurality of fork subgraph structures within a graph structure constructed for a plurality of executable instructions;

means for identifying a plurality of unifiable variables within each fork subgraph structure of said plurality of fork subgraph structures, which are not simultaneously used in said plurality of executable instructions;

means for constructing a dependence graph of said plurality of executable instructions;

means for using said dependence graph to identify at least one unifiable instruction of said plurality of executable instructions, within said plurality of fork subgraph structures; and

means for transferring said at least one unifiable instruction of said plurality of executable instructions from a tine of a corresponding fork subgraph structure of said plurality of fork subgraph structures to a handle of said corresponding fork subgraph structure, said at least one

unifiable instruction containing at least one unifiable variable of said plurality of unifiable variables.

9. (Previously Presented) The system according to claim 8, further comprising:

means for constructing an interference graph structure for a plurality of local variables within said each fork subgraph structure, said plurality of local variables including said plurality of unifiable variables; and

means for identifying said plurality of unifiable variables as variables having overlapping live ranges within said interference graph structure.

10. (Original) The system according to claim 9, wherein said interference graph structure indicates which variables of said plurality of local variables are simultaneously used in said plurality of executable instructions and cannot be unified.

11. (Original) The system according to claim 8, further comprising:

means for constructing a data dependence graph structure for said plurality of executable instructions; and

means for identifying said plurality of unifiable variables using said data dependence graph structure.

12. (Original) The system according to claim 8, further comprising:

means for initializing a flag for said at least one unifiable instruction; and

means for unifying each unifiable variable within said at least one unifiable instruction.

13. (Previously Presented) The system according to claim 12, further comprising:

means for removing said at least one unifiable instruction from subsequent times of said corresponding fork subgraph structure.

14. (Previously Presented) The system according to claim 11, wherein said data dependence graph structure contains a plurality of dependence arcs, each dependence arc connecting two instructions of said plurality of executable

instructions contained within said tine of said corresponding fork subgraph structure.

15. (Currently Amended) A computer readable medium containing instructions, which, when executed in a processing system, cause said processing system to perform a method comprising:

identifying a plurality of fork subgraph structures within a graph structure constructed for a plurality of executable instructions;

identifying a plurality of unifiable variables within each fork subgraph structure of said plurality of fork subgraph structures, which are not simultaneously used in said plurality of executable instructions;

constructing a dependence graph of said plurality of executable instructions;

using said dependence graph to identify at least one unifiable instruction of said plurality of executable instructions, within said plurality of fork subgraph structures; and

transferring said at least one unifiable instruction of said plurality of executable instructions from a tine of a corresponding fork subgraph structure of said plurality of fork subgraph structures to a handle of said

corresponding fork subgraph structure, said at least one unifiable instruction containing at least one unifiable variable of said plurality of unifiable variables.

16. (Previously Presented) The computer readable medium according to claim 15, wherein identifying said plurality of unifiable variables further comprises:

constructing an interference graph structure for a plurality of local variables within said each fork subgraph structure, said plurality of local variables including said plurality of unifiable variables; and  
identifying said plurality of unifiable variables as variables having overlapping live ranges within said interference graph structure.

17. (Original) The computer readable medium according to claim 16, wherein said interference graph structure indicates which variables of said plurality of local variables are simultaneously used in said plurality of executable instructions and cannot be unified.



18. (Original) The computer readable medium according to claim 15, wherein identifying said plurality of unifiable variables further comprises:

constructing a data dependence graph structure for said plurality of executable instructions; and

identifying said plurality of unifiable variables using said data dependence graph structure.

19. (Original) The computer readable medium according to claim 15, wherein said transferring further comprises:

initializing a flag for said at least one unifiable instruction; and

unifying each unifiable variable within said at least one unifiable instruction.

20. (Previously Presented) The computer readable medium according to claim 19, wherein said transferring further comprises:

removing said at least one unifiable instruction from subsequent times of said corresponding fork subgraph structure.

21. (Previously Presented) The computer readable medium according to claim 18, wherein said data dependence graph structure contains a plurality of dependence arcs, each dependence arc connecting two instructions of said plurality of executable instructions contained within said time of said corresponding fork subgraph structure.

22. (Currently Amended) A system comprising:

a memory having stored thereon a plurality of executable instructions to be executed in a program; and

a processor coupled to said memory

to identify a plurality of fork subgraph structures within a graph structure constructed for said plurality of executable instructions;

to identify a plurality of unifiable variables within each fork subgraph structure of said plurality of fork subgraph structures, which are not simultaneously used in said plurality of executable instructions;

to construct a dependence graph of said plurality of executable instructions;

to use said dependence graph to identify at least one unifiable instruction of said plurality of executable instructions, within said plurality of fork subgraph structures; and

to transfer said at least one unifiable instruction of said plurality of executable instructions from a node of a corresponding fork subgraph structure of said plurality of fork subgraph structures to a node of said corresponding fork subgraph structure, said at least one unifiable instruction containing at least one unifiable variable of said plurality of unifiable variables.

23. (Previously Presented) The system according to claim 22, wherein said processor further constructs an interference graph structure for a plurality of local variables within said each fork subgraph structure, said plurality of local variables including said plurality of unifiable variables and further identifies said plurality of unifiable variables as variables having overlapping live ranges within said interference graph structure.

24. (Original) The system according to claim 23, wherein said interference graph structure indicates which variables of said plurality of local variables are simultaneously used in said plurality of executable instructions and cannot be unified.
25. (Original) The system according to claim 22, wherein said processor further constructs a data dependence graph structure for said plurality of executable instructions and identifies said plurality of unifiable variables using said data dependence graph structure.
26. (Original) The system according to claim 22, wherein said processor further initializes a flag for said at least one unifiable instruction and unifies each unifiable variable within said at least one unifiable instruction.
27. (Previously Presented) The system according to claim 26, wherein said processor further removes said at least one unifiable instruction from subsequent tines of said corresponding fork subgraph structure.

28. (Previously Presented) The method according to claim 25, wherein said data dependence graph structure contains a plurality of dependence arcs, each dependence arc connecting two instructions of said plurality of executable instructions contained within said time of said corresponding fork subgraph structure.